

Category 4 Classification

Best Tank. Best Warranty. Best System.

Due to our proprietary blow-molding process and tank design, FRALO tanks are 250% stronger than other poly tanks. They demonstrate structural integrity that exceeds most concrete tanks, all while offering an unmatched 50-year warranty. This milestone is unprecedented for a line of poly septic and pump tanks, and sets the standard for the next generation of onsite wastewater products.

FRALO SEPTTECH™ tanks are 100% watertight, corrosion proof and have a 50-year warranty.

Category 1

Tanks shall be designed for unsaturated soil. Provide for **6" of dry soil cover** over the top of the tank.

Category 2

Tanks shall be designed for partially saturated soil with the saturation at 31 inches below the outlet invert. Provide for **6" of wet soil cover** over the top of the tank.

Category 3

Tanks shall be designed for saturated soil with the saturation at the top of the tank surface. **Provide for 6" of wet soil cover** over the top of the tank.



Category 4

Tanks shall be designed for saturated soil with the saturation at the top of the tank surface. **Provide for 48" of wet soil cover** over the top of the tank.



Integrity Sales & Marketing

5820 Brannen Rd West

Lakeland, FL 33813

(863) 646-3147

www.intsales.com

FRALO SEPTTECH™
Tank ST-1500

Call Toll Free: 866.943.7256



www.fralo.net

The Next Generation of Onsite Wastewater Products.